



AQUAPANEL®

08/2017

AQUAPANEL® Basecoat Primer

Synthetic dispersion with high alkali resistance



Description

AQUAPANEL® Basecoat Primer is used as a primer on AQUAPANEL® Exterior Basecoat and AQUAPANEL® Exterior Basecoat - white where AQUAPANEL® render finishes, e.g. AQUAPANEL® Exterior Silicon Synthetic Resin Plaster – white, AQUAPANEL® Exterior Dispersion Plaster – white or AQUAPANEL® Exterior Mineral Finish white are used on AQUAPANEL® Cement Board Outdoor. It reduces suction variations.

Properties

- High resistance to alkalis
- Dries to white

Preparation of the substrate

The background must be rigid, dry, clean and free of loose parts and peeling residues. The background and air temperature must not be below +5°C during use.

Processing

AQUAPANEL® Basecoat Primer is applied undiluted across the entire surface with a lamb's wool roller or brush. Stir bucket contents occasionally. Leave at least 24 hours between priming and finishing plaster. The primer must be completely dry.

Clean tools and equipment with water immediately after use.

Material coverage

Approx. 100 –150 g/m²

Working time

Approx. 1 minute/m²

Working temperature/climate

The background and air temperature must not be below +5° during use.

Method of delivery/storage

- 15 kg/pail
- Can be stored for approx. 18 months in a frost-free area

Item code: 49299

AQUAPANEL®

www.AQUAPANEL.com

aquapanel.info@knauf.com

© 2017 EN-08/17

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.